

SAFETY DATA SHEET

Creation Date 15-Mar-2010

Revision Date 23-May-2017

Revision Number 2

1. Identification

Product Name 1,6-Hexanediamine

Cat No. : AC120640000; AC120640010; AC120640050; AC120640051;
AC120641000; AC120645000

Synonyms 1,6-Diaminohexane; Hexamethylenediamine

Recommended Use Laboratory chemicals.

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

| | |
|---------------------|---------------------|
| Fisher Scientific | Acros Organics |
| One Reagent Lane | One Reagent Lane |
| Fair Lawn, NJ 07410 | Fair Lawn, NJ 07410 |
| Tel: (201) 796-7100 | |

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|--|--------------|
| Flammable liquids | Category 4 |
| Acute oral toxicity | Category 4 |
| Acute dermal toxicity | Category 4 |
| Skin Corrosion/irritation | Category 1 B |
| Serious Eye Damage/Eye Irritation | Category 1 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Target Organs - Respiratory system. | |

Label Elements

Signal Word

Danger

Hazard Statements

Combustible liquid
Harmful if swallowed
Harmful in contact with skin
Causes severe skin burns and eye damage
May cause respiratory irritation

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Wear protective gloves/protective clothing/eye protection/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth
 Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition / information on ingredients

| Component | CAS-No | Weight % |
|----------------------|----------|----------|
| Hexamethylenediamine | 124-09-4 | >95 |

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Inhalation

Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

| | |
|--|---|
| Ingestion | Do not induce vomiting. Call a physician or Poison Control Center immediately. |
| Most important symptoms/effects | Causes burns by all exposure routes. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated |
| Notes to Physician | Treat symptomatically |

5. Fire-fighting measures

| | |
|---|--|
| Suitable Extinguishing Media | CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire with water spray. |
| Unsuitable Extinguishing Media | No information available |
| Flash Point | 81 °C / 177.8 °F |
| Method - | No information available |
| Autoignition Temperature | 310 °C / 590 °F |
| Explosion Limits | |
| Upper | 6.3 vol % |
| Lower | 0.7 vol % |
| Sensitivity to Mechanical Impact | No information available |
| Sensitivity to Static Discharge | No information available |

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂) Nitrogen oxides (NO_x)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

| Health | Flammability | Instability | Physical hazards |
|--------|--------------|-------------|------------------|
| 3 | 2 | 1 | N/A |

6. Accidental release measures

| | |
|---|--|
| Personal Precautions | Use personal protective equipment. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid dust formation. |
| Environmental Precautions | Should not be released into the environment. See Section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system. |
| Methods for Containment and Clean Up | Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dust formation. |

7. Handling and storage

| | |
|-----------------|---|
| Handling | Wear personal protective equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid dust formation. Do not breathe vapors/dust. Do not ingest. |
| Storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Corrosives area. |

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH | Mexico OEL (TWA) |
|----------------------|--------------|----------|------------|------------------|
| Hexamethylenediamine | TWA: 0.5 ppm | | | |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Engineering Measures Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

| | |
|---|--|
| Physical State | Solid |
| Appearance | Colorless |
| Odor | amine-like |
| Odor Threshold | No information available |
| pH | 12 1% aq. solution |
| Melting Point/Range | 38 - 41 °C / 100.4 - 105.8 °F |
| Boiling Point/Range | 204 - 205 °C / 399.2 - 401 °F @ 760 mmHg |
| Flash Point | 81 °C / 177.8 °F |
| Evaporation Rate | Not applicable |
| Flammability (solid,gas) | No information available |
| Flammability or explosive limits | |
| Upper | 6.3 vol % |
| Lower | 0.7 vol % |
| Vapor Pressure | 2 mbar @ 50 °C |
| Vapor Density | Not applicable |
| Specific Gravity | No information available |
| Solubility | Partly soluble in water |
| Partition coefficient; n-octanol/water | No data available |
| Autoignition Temperature | 310 °C / 590 °F |
| Decomposition Temperature | No information available |
| Viscosity | Not applicable |
| Molecular Formula | C6 H16 N2 |
| Molecular Weight | 116.21 |

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Hygroscopic.

Conditions to Avoid Incompatible products. Avoid dust formation. Exposure to moist air or water. Heat, flames

and sparks.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|----------------------|--------------------------|------------------------------|-----------------|
| Hexamethylenediamine | LD50 = 750 mg/kg (Rat) | LD50 = 1110 mg/kg (Rabbit) | Not listed |

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|----------------------|----------|------------|------------|------------|------------|------------|
| Hexamethylenediamine | 124-09-4 | Not listed |

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|----------------------|---|-----------------------------------|--------------------|---|
| Hexamethylenediamine | EC50: = 14.8 mg/L, 96h (Pseudokirchneriella subcapitata) | Leuciscus idus: LC50: 62 mg/L/96h | EC50 = 85 mg/L 2 h | EC50: = 23.4 mg/L, 48h (Daphnia magna) |

| | | | | |
|--|--|--|--|--|
| | EC50: = 15 mg/L, 72h (Pseudokirchneriella subcapitata) | | | |
|--|--|--|--|--|

Persistence and Degradability Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

| Component | log Pow |
|----------------------|---------|
| Hexamethylenediamine | 0.02 |

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN2280
 Proper Shipping Name HEXAMETHYLENEDIAMINE, SOLID
 Hazard Class 8
 Packing Group III

TDG

UN-No UN2280
 Proper Shipping Name HEXAMETHYLENEDIAMINE, SOLID
 Hazard Class 8
 Packing Group III

IATA

UN-No UN2280
 Proper Shipping Name HEXAMETHYLENEDIAMINE, SOLID
 Hazard Class 8
 Packing Group III

IMDG/IMO

UN-No UN2280
 Proper Shipping Name HEXAMETHYLENEDIAMINE, SOLID
 Hazard Class 8
 Packing Group III

15. Regulatory information

International Inventories

| Component | TSCA | DSL | NDSL | EINECS | ELINCS | NLP | PICCS | ENCS | AICS | IECSC | KECL |
|----------------------|------|-----|------|-----------|--------|-----|-------|------|------|-------|------|
| Hexamethylenediamine | X | X | - | 204-679-6 | - | | X | X | X | X | X |

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313 Not applicable

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute Health Hazard | Yes |
| Chronic Health Hazard | No |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act) Not applicable

Clean Air Act Not applicable

OSHA Occupational Safety and Health Administration
Not applicableCERCLA
Not applicable

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|----------------------|---------------|------------|--------------|----------|--------------|
| Hexamethylenediamine | X | X | - | - | - |

U.S. Department of Transportation

| | |
|-----------------------------|---|
| Reportable Quantity (RQ): | N |
| DOT Marine Pollutant | N |
| DOT Severe Marine Pollutant | N |

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Moderate risk, Grade 2

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 15-Mar-2010**Revision Date** 23-May-2017**Print Date** 23-May-2017**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information

relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS